



SA106B-XX

www.sac-ontop.com.tw

6W Switching Adapter with Exchangeable AC Plug

Input

Rated Voltage	100 - 240 VAC
Max. Voltage	90 - 264 VAC
Line Frequency	47 - 63 Hz
Current	250mA at 100-240VAC
Configuration	2PIN

Output

Model Name	Voltage	Current	Watt	Efficiency
SA106B-05	5V	1.2A	6W	67%
SA106B-09	9V	0.7A	6.3W	70%
SA106B-12	12V	0.5A	6W	70%
Line Regulation	Less than $\pm 2\%$			
Load Regulation	Less than $\pm 5\%$			
Protections	OCP, OVP & Short circuit			
Ripple & Noise	$\leq 100\text{mVp-p}$, (For 5V, 9V models) $\leq 120\text{mVp-p}$, (For 12V model)			

Environment

Operating Temp.	0°C - 40°C
Storage Temp.	-20°C - 80°C
Humidity	10% - 90% (Non-condensing)
RoHS & WEEE	Standard

Reliability

MTBF	50,000 hrs (MIL-217 Standard)
Safety	ITE: UL, cUL, TUV, CE, CB

Others

Package	TBD pcs/box
Min. Order	1K pcs/lot
Warranty	1 year

For reference only. For details please contact your local sales representative

Electrical

Topology	Switching Mode
Hi-Pot	3000 Vac/1sec @ 5mA (primary - secondary)
Leakage Current	$\leq 0.25\text{mA}$, at 264VAC/50Hz
Hold Up Time	≥ 6 mSec
Standby Power	≤ 0.3 Watt
EMI	Complies with EMI directives
Energy Star Requirement	EPS 2.0 (Efficiency Level V)
ErP Requirement	Efficiency Level : Stage 2
MEPS Requirement	Efficiency Level : V (9V only comply with CEC IV, ErP Stage 1, MEPS IV)

Mechanical

Case Size	58L x 45W x 34H mm
Case Material	Black, 94V-1 or equivalent
Weight	86 ± 5 g
DC Cord	4.92ft

