



A124C-XXU

www.sac-ontop.com.tw

24W Switching Adapter Series

Input					Electrical	
Rated Voltage	100 - 240 VAC				Topology	Switching Mode
Max. Voltage	90 - 264 VAC				Hi-Pot	3000 Vac/1sec @ 5mA (primary - secondary)
Line Frequency	47 - 63 Hz				Leakage Current	$\leq 0.25\text{mA}$, at 264VAC/60Hz
Current	800mA, at 100-240VAC				Hold Up Time	≥ 8 mSec
Configuration	IEC-320, C8, 2PIN				Standby Power	≤ 0.3 Watt (As per CEC Consumption Guideline)
Output					Mechanical	
Model Name	Voltage	Current	Watt	Efficiency	Case Size	78L x 50W x 30H mm
SA124C-12U	12V	2.0A	24W	78%	Case Material	Black, 94V-1 or equivalent
SA124C-15U	15V	1.6A	24W	78%	Weight	132, ± 10 g
SA124C-24U	24V	1.0A	24W	78%	DC Cord	4.92ft
Line Regulation	Less than $\pm 2\%$					
Load Regulation	Less than $\pm 5\%$					
Protections	OCP, OVP & Short circuit					
Ripple Voltage	$\leq 1\%V_o$.					
Environment						
Operating Temp.	0°C - 40°C					
Storage Temp.	-20°C - 80°C					
Operating Humidity	20% - 80% (Non-condensing)					
Reliability						
MTBF	50,000 hrs (by MIL-217 Standard)					
Safety	ITE: UL, cUL, TUV/GS, CB, CE, PSE					
Others						
Package	80 pcs/box					
Min. Order	1K pcs/lot					
Warranty	1 year					
For reference only. For details please contact your local sales representative						